



Version: 20.Feb.2008

Resistant Contour- and Coating Colours

Firing range 580°- 620° C

Page:

1/1

Opaque, resistant colours

Range of application:

Stained glass, Restoration, Contours, Coatings (Modellings)

Indication	Type Nr.	Surface at 600°C
Contoure grey green	F 1589	matt
Contoure black green	F 1591	satin matt
Contoure black	DN	satin matt
Contoure black	F 4102	satin matt
Contoure black	F 4104	satin gloss
Contoure black	F 4108	matt
Contoure dark brown	F 6322	matt
Contoure dark brown	F 6334	satin gloss
Contoure red brown	F 6359	matt
Contoure iron red	F 6360	satin gloss
Contoure maron	F 6363	satin gloss
Contoure sepia	F 6371	matt

Please Note:

The information in this leaflet are based on our current knowledge and experience. This description does not release the users from examinations and tests of their own because of uncountable possible influences, when using and applying the products in connection with every other material being involved in the production. It can not be deduced a legally obliged assurance for specific characteristics or for the aptitude of a definite usage purpose. The receiver of our products has to observe by his own responsibility probable protecting rights as well as existing laws, rules and regulations.

CRG Srl Via Monte Bianco 81 41042 Fiorano Modenese (MO) ITALY

Tel.: +39 0536 845220