



Version: 20. Jul. 2016

Fast- Fire Inglaze Colours "IS"- Series

Firing Temperature 1000°- 1250° C

Page:

1/1

Resistant Inglaze Colours

Range of application: Household-porcelain, Hotel-porcelain, Tiles

Indication	Type number	Pantone Nr.
Flux	F 9147	
White	IS 9174	white
Relief-White	IS 9176	white
Light Yellow	IS 3330	102 C
Yellow	IS 3800	Yellow C
Light beige	IS 3332	1215 C
Yellowish orange	IS 3334	149 C
Beige	IS 3333	142 C
Red	IS 7295	7416 C
Orange	IS 7800	Oran. 21 C
Red	IS 7801	179 C
Dark Red	IS 7802	187 C
Yellowish brown	IS 6330	145 C
Brown	IS 6333	464 C
Red violet	IS 7279	686 C
Blue violet	IS 7280	2635 C
Violet	IS 7281	521 C
Aubergine	IS 7296	492 C
Dark purple	PH 263	209 C
Light blue	IS 2421	2985 C
Light blue	IS 2422	543 C
Blue	IS 2423	542 C
Blue	IS 2427	2945 C
Blue	IS 2443	661 C
Cobalt blue	IS 2428	653 C
Dark blue	IS 2430	2955 C
Dark Cobalt blue	IS 2429	295 C
Green	IS 1550	7494 C
Green	IS 1553	625 C
Dark green	IS 1560	329 C
Dark grey	IS 5218	7542 C
Blue grey	IS 5217	7543 C
Brown grey	IS 5216	407 C
Grey	IS 5215	w. grey 6 C
Grey	IS 5220	444 C
Black grey	IS 5221	Black 7
Black	IS 4094	black C

Please Note:

The information in this leaflet are based on our current knowledge and experience. This description does not release the users from examinations and tests of their own because of uncountable possible influences, when using and applying the products in connection with every other material being involved in the production. It can not be deduced a legally obliged assurance for specific characteristics or for the aptitude of a definite usage purpose. The receiver of our products has to observe by his own responsibility probable protecting rights as well as existing laws, rules and regulations.

CRG Srl Via Monte Bianco 81 41042 Fiorano Modenese (MO) ITALY

Tel.: +39 0536 845220