



Delivery Program Version: 20.Jul. 2016	Paints for Colour Break Firing range 540°- 600° C	Page: 1/1
--	---	---------------------

Opaque, semiresistant Colours

Range of application:

Nominal breaking point on ampoules

Indication	Type Nr.	Pantone-Nr.	suitable Colour for Printing
Flux	FL 218/ 35/ 0480	-	-
White	F 9114/ 35/ 0480	-	F 9143
Yellow	F 3300/ 35/ 0480	108 C	F 3325
Red	F 7258/ 35/ 0480	179 C	F 7064/I
Dark red	F 7244/ 35/ 0480	704 C	F 7042
Light blue	F 2337/ 35/ 0480	2718 C	F 2208
Dark blue	F 2210/ 30/ 0480	7455 C	P 2736
Green	F 1422/ 35/ 0480	364 C	F 1654
Blue green	F 1584/ 35/ 0480	3415 C	F 1535
Dark grey	F 5182/ 35/ 0480	445 C	F 5196
Black	F 4087/ 35/ 0480	419 C	F 4044

Please Note:

The informations in this leaflet are based on our current knowledge and experience. This description does not release the users from examinations and tests of their own because of uncountable possible influences, when using and applying the products in connection with every other material being involved in the production. It can not be deduced a legally obliged assurance for specific characteristics or for the aptitude of a definite usage purpose. The receiver of our products has to observe by his own responsibility probable protecting rights as well as existing laws, rules and regulations.

Rüger & Günzel GmbH
 Dornhofstrasse 71
 D 63263 Neu-Isenburg
 Tel: +49(0)6102-812940
 Fax: +49(0)6102-8129440
 E-Mail: info@rgfarben.de