



Color Chart

Version: 1.June 2010

**Leadfree Inglaze – Fast-Firing
 Colors Serie „IB“**

Firing Range 1000°- 1280° C

Page:

1/1

The Colour Chart shows an approximate impression of the basic colours for a first selection of colours. For exact reproduction of a colour tone it is absolutely necessary to test a sample under original conditions.

Mixing White IB 9610	White IB 9680	Lemon Yellow IB 3610 Pant. 386C	Yellow IB 3620 Pant. YellowC	Orange IB 7600 Pant. OrangeC	Light Red IB 7610 Warm Red C
Dark Red IB 7630 Pant. 180C	Purple IBP 7677 Pant. 7433C	Bordeaux IB 7670 Pant. 492C	Lila IB 7622 Pant. 2563C	Light Blue IB 2620 Pant. 297C	Blue IB 2640 Pant. 295C
Dark Blue IB 2630 Pant. 2755C	Turquoise IB 1621 Pant. 331C	Leaf Green IB 1620 Pant. 7483C	Chrom Green IB 1622 Pant. 574C	Fir Green IB 1623 Pant. 330C	Light Brown IB 6610 Pant. 158C
Orangebrown IB 6630 Pant. 167C	Brown IB 6620 Pant. 168C	Dark Brown IB 6640 Pant. 476C	Black IB 4640 Pant. BlackC	Blue-Grey IB 5620 Cool Grey 6C	Beige-Grey IB 5660 Pant. 407C

Please Note:

The information in this leaflet are based on our current knowledge and experience. This description does not release the users from examinations and tests of their own because of uncountable possible influences, when using and applying the products in connection with every other material being involved in the production. It can not be deduced a legally obliged assurance for specific characteristics or for the aptitude of a definite usage purpose. The receiver of our products has to observe by his own responsibility probable protecting rights as well as existing laws, rules and regulations.

Rüger & Günzel GmbH
 Dornhofstrasse 71
 D 63263 Neu-Isenburg
 Tel: +49(0)6102-812940
 Fax: +49(0)6102-8129440
 E-Mail: info@rgfarben.de